



ELEVATORI IDRAULICI TRIPLEX

Triples hydraulic forklifts

CM 16THAD



Elevatore idraulico per trattori di media potenza. Dotato di alzata libera che consente di sollevare il carico senza variare l'ingombro.

- Cuscinetti radiali a rulli cilindrici
- Quattro catene di sollevamento "Fleyer"
- Profili in acciaio ad "U" ed "H" laminati a caldo
- Cilindro di sollevamento a doppio effetto
- Attacco a tre punti cat. 2
- Alzata libera 200 mm
- Distributore idraulico a 4 leve
- Traslatore laterale a scorrimento su boccole autolubrificanti
- Forche pieghevoli e regolabili
- Cilindro di brandeggio con snodo regolabile
- Tubi di collegamento al trattore

Hydraulic forklift suitable to medium power tractors. Equipped with free lifting for raising the load without changing overall dimensions.


- *Cylindrical roller bearings*
- *Four "Fleyer" lifting chains*
- *"U" and "H" shaped hot rolled steel profiles*
- *Double effect lifting cylinder*
- *Cat.2 three point linkage*
- *Free lifting 200 mm*
- *Distributor with 4 levers*
- *Side shift sliding on self-lubricating bushes*
- *Adjustable and pliable forks*
- *Tilting cylinder with adjustable junction*
- *Connecting hoses to the tractor*



Cuscinetti radiali a rulli cilindrici
Straight roller radial bearings



Catene di sollevamento tipo "Fleyer"
"Fleyer" type lifting chains




Distributore 4 leve
Distributor with 4 levers



Forche pieghevoli e regolabili
Adjustable and pliable forks



Traslatore laterale
Side shift



Alzata libera
Free lifting



Profili in acciaio laminati a caldo
Hot-rolled steel profiles

CM16THAD				
MODELLO <i>Model</i>	PORTATA <i>Load capacity</i>	ALTEZZA SOLLEVAMENTO <i>Lifting height</i>	INGOMBRO <i>Overall dimensions</i>	PESO <i>Weight</i>
	Kg	mm	mm	Kg
16THAD 2000	1600	2000	1315	370
16THAD 2500	1600	2500	1480	390
16THAD 2800	1600	2800	1580	425
16THAD 3000	1600	3000	1650	445
16THAD 3200	1600	3200	1730	465
16THAD 3600	1600	3600	1850	510

NEW!

